



Soft Pneumatic Manipulator with Stiffness Tuning Capability

Preston Fairchild, Yu Mei, Angela Burns, Noah Shephard, Samuel Rabick, Xiaobo Tan
Department of Electrical and Computer Engineering, Michigan State University, East Lansing, MI

Introduction

Objective

- Design and fabricate a soft robot with manipulation and stiffness tuning capability that is controllable via pneumatics


Challenges

- High compliance with large payload causes deformation
- Precise control of arm via pneumatics
- Wide range of stiffness possibilities to control around




Pneumatic Control

- PID control of individual chambers on manipulator
- Operating pressure of up to 120KPA




Stiffness Tuning

- Variable stiffness enables the soft robot to take advantage of providing stable end-effector positioning, storing energy within the system to rapidly accelerate, and handle larger payloads
- Particle jamming mechanism with multiple variations and combinations of particles tested.




- Independent control by small vacuum pump to create negative pressure and jam particles increasing stiffness



- Coordinated control of actuation and stiffness-tuning continues to be a key focus.

Results

- Stiffness tuning reduces the effects of external disturbances such as payload
- Bending force sufficient to lift target weight (apple)




- Capable of achieving 90° bending angle
- Multiple chambers can be inflated in conjunction to control the direction of bending
- All chambers can be inflated to create elongation of the manipulator



Fabrication

3D Printed Mold

- Mold model for robotic arm designed in CAD
- Mold parts 3D printed from lab printer using PLA and assembled for casting



Silicone Casted Arm

- Manipulator casted from Dragonskin 20™ silicone
- Silicone caps made for sealing air chambers and connecting pneumatic tubing



Future Work

- Add additional segments for larger and more accessible workspace
- Implement higher level control and path planning algorithms to accomplish tasks utilizing stiffness tuning

Acknowledgements

This work was supported in part by the National Science Foundation (ECCS 2024649) and the Michigan State University Strategic Partnership Grants program (16-SPG-Full-3236).